

LONG DISTANCE INTRASTATE TELECOMMUNICATIONS SERVICE

3. GENERAL RULES AND REGULATIONS (Cont'd)7 EQUIPMENT (Cont'd)

3.7.1 Customer obligations (Cont'd)

3.7.1.3 The Customer shall operate its equipment and facilities in such a manner that its use of the Company's facilities shall not interfere with any other Customer's use of the Company's services or equipment.

3.7.1.4 The Customer shall provide adequate space, electrical power, wiring, HVAC and electrical outlets necessary for the proper operation of the Company's equipment on the Customer's and/or authorized user's premises.

3.7.1.5 The Customer shall be responsible for all loss regardless of cause (other than directly resulting from an act or omission of the Company) to the Company's equipment on the Customer's or its authorized user's premises.

3.7.1.6 The Customer is responsible for ensuring that, except for Customer authorized and qualified personnel, no one attempts to adjust, modify, move or otherwise interfere in any way with the continuous operation of the Company's equipment located at the Customer's or authorized user's premises.

3.7.1.7 The Customer shall comply with the minimum protective criteria generally accepted in the telephone industry and other appropriate criteria as may be prescribed by the Company to protect the integrity of service or for safety reasons.

3.7.1.8 The Customer shall be responsible for the installation, operation or maintenance of any Customer-provided equipment. Where such equipment is connected to service furnished pursuant to this price list, the responsibility of the Company shall be limited to the furnishing of services under this price list and to the maintenance and operation of such services in the proper manner. Subject to this responsibility, the Company shall not be responsible for the following:

- (a) the through transmission of signals generated by Customer-provided equipment or for the quality of, or defects in, such transmission.
- (b) the reception of signals by Customer-provided equipment; or
- (c) network control signaling where such signaling is performed by Customer-provided network control signaling equipment.